



2-PACK POLYURETHANE VARNISH

2 Component Clear Floor Varnish

Description

A superior quality clear floor varnish for interior surfaces. Suitable for high wear wooden floors and parquet (not suitable for laminate/synthetic parquet).

Technical Specifications

Vehicle type	:	Polyester Polyod
Specific Gravity	:	0.99±0.02
Weight solids	:	43±1%
Viscosity	:	10"-15" Ford cup No.4
Gloss	:	>80 at 20°, GLOSS (EN13300)
Coverage (on a smooth surface)	:	9-11 m ² /L / coat
Dilution	:	For brush or roller: up to 10%, by volume For Airless spray: up to 20%, by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 2-3 hours Recoat: 12-24 hours depending on weather conditions
Flash point	:	<60°C
EU limit value for this product (cat. A/j): 500g/l (2010). This product contains max 490g/l VOC		

Instructions for Use

SURFACE PREPARATION

Remove all surface contamination, e.g. dust, oil stains and dampness by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Peeling or cracked varnish should be scraped off and sanded in the direction of the woodgrain to a sound surface.

APPLICATION

Thinning/Cleaning: Thinner 11/11 (Peletico's product).

Application tools: Brush, roller or airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

2-PACK POLYURETHANE VARNISH (Component A) should be mixed together thoroughly with **CATALYST 269/1** (Component B) and allow to stand for 5-10 minutes before application. Due to a limited pot life the mixture should be used within 24 hours. It is recommended to apply 3 coats. After the first coat allow 12-24 hours between the subsequent coats. Sanding in the direction of the woodgrain, is recommended between coats. Attains maximum hardness after approximately 2-3 days from application, depending on weather conditions.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with Thinner.

PACKING: **2-PACK POLYURETHANE VARNISH:** 1L, 2.5L & 4L.
CATALYST 269/1: 0.5L, 1.25L & 2L.

COLOUR: Clear.



STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

Health and Safety Measures

- Keep out of reach of children.
- Flammable liquid and vapour.
- Causes skin irritation.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves / eye protection / face protection.
- IF ON SKIN OR HAIR: take off immediately all contaminated clothing. Rinse skin with water / shower.
- If skin irritation occurs get medical advice / attention and show the container or label.
- In case of fire: use dry powder extinguisher to extinguish.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus product into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*

